

Case 1 : Installed Items : Modular Universal Rubber Bump Stops UB1A223A **Ground Lifting Height :** 2.3"

Case 2 : Installed Items : Modular Universal Rubber Bump Stops UB1A2223A **Ground Lifting Height :** 2.65"

IMPORTANT NOTICE: RUBBERSHOX INSTALLERS SHOULD APPLY COMMON AUTOMOTIVE SAFETY PRACTICES WHEN RAISING, LOWERING AND WORKING ON VEHICLES, ALWAYS WEARING SAFETY GLASSES, USING BOTH HYDRAULIC JACK AND JACK STAND DURING THE INSTALLATION. We recommend that this installation be done by a professional or person with auto mechanical knowledge. RubberShox Universal Bump Stops are designed to work with original factory springs only. These instructions are general guide line. RubberShox assumes no liability for actual installation process. Rubbershox does not recommend exceed the maximum load recommended by vehicles manufacturer (GVWR)

Original Bump Stops



Case 1 Installed Items : Modular Universal Rubber Bump Stops UB1A223A (UB1A+UB2+UB2+UB3A)
Ground Lifting Height : 2.3"



Case 2 Installed Items : Modular Universal Rubber Bump Stops UB1A2223A (UB1A+UB2+UB2+UB2+UB3A)
Ground Lifting Height : 2.65"

